

Personal Cinema e-GeForce4 MX 440-8X 64MB 064-A8-NV88



AT A GLANCE

- 256-bit GeForce4 MX 440-8X (275MHz clock)
- 64MB 3.6ns 128-bit DDR Memory (250MHz clock - 500MHz effective)
- AGP 8X/AGP 4X Compatibility
- PC 99 DB-15 analog connector (VESA DDC2B + DPMS)
- Philips SAA7133HL for Video Capture In/Out
- Philips FQ1236/F TV Tuner (coaxial out)
- DVI Connector for Analog/Digital Display
- 34 Million Triangles / Sec. (chipset spec)
- 1.1 Billion Texels / Sec. (chipset spec)
- 8.0GB per Second Memory Bandwidth
- Digital Media Hub for Audio/Video Input/Output



Personal Cinema - e-GeForce4 MX 440-8X 64MB

www.evga.com - The Definitive VGA Online Community

2D/3D FEATURES

- NVIDIA Accuview™ Antialiasing - includes FSAA (2X, 4X, 4XS, and Quincunx)
- Integrated Hardware Transform and Lighting engine (T&L)
- NVIDIA Shading Rasterizer™
- True Reflective Bump Mapping
- Cube Environment Mapping
- 32-bit Color with 32-Bit Z/Stencil Buffer
- DirectX® and S3TC® texture compression
- High Performance 2D Rendering engine
- Multi-Buffering (Double, Triple, Quad)
- 2 dual-rendering pipelines
- 4 texels per clock cycle

OTHER FEATURES

- Lightspeed Memory Architecture™ II
- NVIDIA nView™ Multi-Display Technology
- NVIDIA Video Processing Engine™ (VPE)
- Integrated TV Encoder 10-Bit DAC
- Video Acceleration (DirectShow, MPEG-1, MPEG-2, Indeo, MS Bob and Weave)
- High-quality HDTV/DVD playback
- Integrated Dual 350MHz RAMDACs
- Integrated Dual-Channel TMDs Transmitters
- MPEG-2 Motion Compensation
- Interlaced video field support (5-tap horizontal, 3-tap vertical)
- Digital Vibrance Control™ (DVC)

RESOLUTION CHART

	8-Bit	16-Bit	32-Bit
640 x 480	240Hz	240Hz	240Hz
800 x 600	240Hz	240Hz	240Hz
1024 x 768	240Hz	240Hz	200Hz
1152 x 864	200Hz	200Hz	170Hz
1280 x 960	170Hz	170Hz	150Hz
1280 x 1024	170Hz	170Hz	150Hz
1600 x 1024	120Hz	120Hz	100Hz
1600 x 1200	120Hz	120Hz	100Hz
1920 x 1080	100Hz	100Hz	85Hz
1920 x 1200	100Hz	100Hz	85Hz
1920 x 1440	85Hz	85Hz	75Hz
2048 x 1536	75Hz	75Hz	60Hz

Refresh rates shown are the highest obtainable and are monitor dependent.
Resolutions, pixel depths and refresh rates are driver dependent and may not be available in all applications or operating system.
*Patent Pending. Property of eVGA.com Corp.

DRIVER SUPPORT

- AutoInstaller with ADM* Technology
- ResChanger©
- NVIDIA Unified Driver Architecture (UDA) (Windows ME/2000/XP)
 - Direct Draw
 - Direct3D
 - DirectVideo
 - DirectX
- Full OpenGL ICD for All Supported Operating Systems

DIMENSIONS

- height: 4.4in - 110mm
- length: 7in - 175mm

2900 Saturn Street, Suite B Brea, CA 92821
Phone: (888) 881-eVGA Fax: (714) 528-4501

Product Specs

012903